

SYNTHETIC TURF PRODUCT SPECIFICATION SHEET

| <u>PRODUCT</u> | <u>DESCRIPTION</u> |
|---------------------|---|
| TP Match Pitch | A dense polypropylene surface designed for cricket. |
| Infill Rate Sand | N/A |

| <u>YARN SPECIFICATION</u> | |
|---------------------------|-----------------------------|
| Type | UV stable KDK Polypropylene |
| Dtex | 9600 |
| Colour | Sports Green |

| <u>PILE SPECIFICATION</u> | |
|---------------------------|----------|
| Pile Weight | 1100 gsm |
| Pile Height | 7 mm |
| Total Height | 9 mm |
| Machine Gauge | 3/16 |
| Total Tufts/sqm | 47, 850 |

| <u>BACKING SPECIFICATION</u> | |
|------------------------------|---|
| Primary Backing | 100% woven UV resistant polypropylene with fleece. 145gsm Fibre Glass reinforcing scrim A concentrated water resistant SBR latex compound for maximum tuft lock. |
| Primary Backing 2 | |
| Secondary Backing | |

| <u>MANUFACTURED ROLLS</u> | |
|---------------------------|----------|
| Width | 2.74 m |
| Weight/lm | 6.03 kg |
| Total Weight sqm | 2200 gsm |

| <u>GUARANTEE</u> | |
|---|--|
| Leigh Spinners Ltd offer a 5 year guarantee with this product, please refer to Leigh Spinners for conditions. | |

| <u>INSTALLATION AND MAINTENANCE</u> | |
|---|--|
| This product should be installed and maintained in accordance to the products installation and maintenance guide. Details available upon request. | |